

WHAT IS CLAIMED IS:

1. A method for representing geographic features in a computer-based system,
5 comprising:

providing a first computer-usable database storing a plurality of data points
specifying coordinates of locations along at least one geographic feature;

fitting a polynomial spline to the at least one geographic feature by applying a
least squares approximation to the data points to generate a plurality of control points for the
10 polynomial spline; and

storing the control points in a second computer-usable database, the control points
being usable for representing the geometry of the at least one geographic feature in the
computer-based system.

15 2. The method of claim 1, wherein the data points are selected from the group
consisting of coordinate pairs and coordinate triples.

3. The method of claim 1, further comprising:
configuring the number of control points.

20 4. The method of claim 1, wherein the polynomial spline is selected from the group
consisting of uniform nonrational B-spline, non-uniform nonrational B-spline, uniform
Catmull-Rom spline, nonuniform Catmull-Rom spline, and NURBS.

25 5. The method of claim 1, further comprising:
defining a knot sequence for the polynomial spline.

6. The method of claim 5, further comprising:
manually defining the knot sequence.

30 7. The method of claim 5, further comprising:
storing the knot sequence in the second computer-usable database.

8. The method of claim 1, further comprising:
incorporating in the least squares approximation a bearing value associated with a
node included in the plurality of data points.

5

9. The method of claim 1, further comprising:
weighting a node included in the plurality of data points in the least squares
approximation.

10

10. The method of claim 1, further comprising:
employing regularization in computing the least squares approximation.

15
20
25
30
35
40
45
50
55
60
65
70
75
80
85
90
95
100
105
110
115
120
125
130
135
140
145
150
155
160
165
170
175
180
185
190
195
200
205
210
215
220
225
230
235
240
245
250
255
260
265
270
275
280
285
290
295
300
305
310
315
320
325
330
335
340
345
350
355
360
365
370
375
380
385
390
395
400
405
410
415
420
425
430
435
440
445
450
455
460
465
470
475
480
485
490
495
500
505
510
515
520
525
530
535
540
545
550
555
560
565
570
575
580
585
590
595
600
605
610
615
620
625
630
635
640
645
650
655
660
665
670
675
680
685
690
695
700
705
710
715
720
725
730
735
740
745
750
755
760
765
770
775
780
785
790
795
800
805
810
815
820
825
830
835
840
845
850
855
860
865
870
875
880
885
890
895
900
905
910
915
920
925
930
935
940
945
950
955
960
965
970
975
980
985
990
995

11. The method of claim 1, further comprising:
identifying a straight section of the at least one geographic feature; and
storing in the second computer-usable database the data points corresponding to
the straight section.

12. The method of claim 11, further comprising:
computing the control points only for one or more curved sections of the at least
one geographic feature.

13. The method of claim 11, further comprising:
computing the control points such that the tangent to the spline approximation of
a curved section of the at least one geographic feature and the tangent to the straight section are
equal at the point at which the curved and straight section meet.

14. A method of displaying on a computer output device a function representing a
geographic feature, comprising:

retrieving from a computer-usable database a plurality of spline control points
associated with the geographic feature, the spline control points being derived, using a least
squares approximation, from a plurality of data points specifying coordinates of locations along
the geographic feature;

calculating a polynomial spline using the spline control points to generate the function representing the geometry of the geographic feature; and
displaying the function on the computer output device.

5

15. The method of claim 14, wherein the polynomial spline is selected from the group consisting of uniform nonrational B-spline, non-uniform nonrational B-spline, uniform Catmull-Rom spline, nonuniform Catmull-Rom spline, and NURBS.

10

16. A method of generating a computer-usable database that represents feature geometry using a plurality of spline control points associated with a plurality of geographic features, comprising:

providing a predetermined database that represents feature geometry using a plurality of data points specifying coordinates of locations along the geographic features;

15

for each of the geographic features, retrieving a corresponding set of data points from the predetermined database;

20

fitting a polynomial spline to each of the geographic features by computing a plurality of control points yielding the least squares approximation to the corresponding set of data points; and

25

storing the plurality of spline control points in the computer-usable database.

30

17. The method of claim 16, further comprising:

identifying a straight section of a geographic feature based on the data points; and

storing in the computer-usable database the data points corresponding to the

35

straight section of the geographic feature.

18. The method of claim 17, further comprising:

computing the control points only for one or more curved sections of the geographic feature.

40

19. The method of claim 17, further comprising:

computing the control points for a geographic feature that has a curved section and an adjoining straight section such that a bearing value at an endpoint of the curved section equals a corresponding bearing value at an endpoint of the straight section that meets the curved section.

20. The method of claim 16, further comprising:
incorporating in the least squares approximation a bearing value associated with a node included in the plurality of data points.

21. The method of claim 16, further comprising:
weighting a node included in the plurality of data points.

22. The method of claim 16, further comprising:
employing regularization in the least squares approximation.

23. A system for displaying a function representing the geometry of a geographic feature, comprising:
a database storing one or more spline control points associated with the geographic feature, the spline control points being derived, using a least squares approximation, from a plurality of data points specifying coordinates of locations along the geographic feature;
a processor configured to compute a polynomial spline using the spline control points to generate the function representing the geometry of the geographic feature; and
a display device for displaying the polyline.

24. The system of claim 23, wherein the spline control points are derived by incorporating in the least squares approximation a bearing value associated with a node included in the plurality of data points.

25. The system of claim 23, wherein the spline control points are derived using the least squares approximation by weighting a node included in the plurality of data points.

26. The system of claim 23, wherein the spline control points are derived by employing regularization in the least squares approximation.

27. The system of claim 23, wherein the processor is configured to determine whether the geographic feature includes a straight section, and if so, linearly interpolate the data points representing the straight section.

28. The system of claim 23, wherein the polynomial spline is selected from the group consisting of uniform nonrational B-spline, nonuniform nonrational B-spline, uniform Catmull-Rom spline, nonuniform Catmull-Rom spline and NURBS.

29. A system for generating a plurality of spline control points that represent feature geometry, comprising:
a first computer-usable database for storing a plurality of data points specifying coordinates of locations along at least one geographic feature;
a processor configured to apply a least squares approximation to the data points to generate the plurality of control points for a polynomial spline; and
a second computer-usable database for storing the control points.

30. The system of claim 29, wherein the processor is configured to incorporate in the least squares approximation a bearing value associated with a node included in the plurality of data points.

31. The system of claim 29, wherein the processor is configured to weight a node included in the plurality of data points in the least squares approximation.

32. The system of claim 29, wherein the processor is configured to employ regularization in computing the least squares approximation.

33. The system of claim 29, wherein the processor is configured to determine whether the at least one geographic feature has a substantially straight section, and if so, to store in the second computer-usable database the data points corresponding to the straight section.

5

34. The system of claim 33, wherein the processor computes the control points only for one or more curved sections of the at least one geographic feature.

35. The system of claim 29, wherein the polynomial spline is selected from the group
10 consisting of a uniform nonrational B-spline, nonuniform nonrational B-spline uniform Catmull-Rom spline, nonuniform Catmull-Rom spline, and NURBS.

005021-6262260